

ZoneVu ZVK-66D Keyboard

DIGITAL-IP

ANALOGUE 🗸

HYBRID 🗸



Features

3-axis fully proportional joystick for precision camera and dome control IP compatible when used in conjunction with a Fusion-Core enabled workstation Ergonomically designed to reduce RSI Functions as a 'neutral handed' joystick when used with the ZVK-77D keyboard Fully supported by Fusion-Core VMS software application Compatible with ZoneVu integrated video systems Fully Auditable with Meyertech's Fusion Audit software application



The ZoneVu ZVK-66D Keyboard

Product Overview

Integrated LED status indicators

The ZVK-66D is a key addition to the ZoneVu product portfolio providing the familiar ZoneVu 'touch & feel' for systems which are managed by Fusion-Core, Meyertech's Video Management Software (VMS) application.

Designed and manufactured to the same exacting standards set by the ZVK-77D the ZVK-66D incorporates a 3-axis variable speed control joystick for precise control of both analogue and IP cameras and domes.

The joystick technology employed in the ZVK-66D is fully proportional providing the operator with independent variable speed control of Pan, Tilt, Zoom, Focus and Iris functions. It also has a centre-mounted button allows users to quickly select between lens functions.

When the ZVK-66D keyboard is connected to a Fusion-Core enabled workstation control of cameras and domes becomes simpler and more intuitive for users allowing control of thousands of cameras across multiple sites. The ZVK-66D can also be used in conjunction with the ZVK-77D to provide a 'neutral-handed' solution for users who are left-handed.

PB-ZVK-66-20110901 Web: www.meyertech.co.uk Tel: +44(0)161 643 7956 Email: sales@meyertech.co.uk © Meyertech Limited 201



SECURITY with VISION

Zone Vu ZVK-66D Keyboard Specification

ANALOGUE 🗸





Specification

Enclosure - Ergonomic low profile design incorporating 55mm wrist support; constructed from extruded aluminium, mild-steel and plastic, the base of the enclosure incorporates anti-slip rubber strips.

Enclosure overlay - Hard coat gloss polyester - UV varnish finish Dimensions - W125mm D315mm H113mm including joystick, 85mm excluding joystick

Weight - 1Kg

Power Input - External PSU. Universal input 90 - 264VAC IEC320 AC inlet class 1. Overload and over-voltage protection with short circuit protection.

UL, cUL, TUV, CE approvals 12V 15W output

Power Consumption - Less than 15W

Temperature - Storage 0°C to +50°C. Operating 0°C to +40°C. Humidity 10% to 95% non condensing

Serial Communication - RS485 full-duplex

Joystick - Proportional 3-axis 300 deg. Rotation with pushbutton control.

Self centring spring action.

Lifetime - rotational cycles > 1 million.

Rear Panel Connectors - ZoneVu Port - 7-pin DIN socket incorporating

low voltage DC power connection

MTBF - 31,000 Hours

Configuration - Set up via Fusion Core application

Status LED's - Green Zoom mode, Focus mode and Iris mode indicator LED's.

Red Telemetry transmission and ZoneVu network present LED's. Blue CPU heartbeat LED





SECURITY with VISION

ZoneVu ZVK-66D Keyboard Specification



DIGITAL-IP

ANALOGUE 🗸

HYBRID 🎺

INTEGRATED VIDEO SYSTEMS

Ordering Information

ZVK-66D - ZoneVu Desktop Operator Keyboard. Designed primarily to operate in PCI mode with FUSION workstations as a camera controller it incorporates a 3-axis Joystick to control PTZ, F and I camera functions, ergonomic integrated wrist support to minimise RSI and status LED's.

ZVK-66D-PSU - ZVK-66D PSU. Input 99-264VAC 50-60Hz. Output 12VDC



The purpose of this data sheet is to provide product information on Meyertech products. The information in this datasheet is believed to be accurate and reliable. However, no responsibility or liability is assumed by Meyertech Limited for its use, or for any infringement of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or other rights of Meyertech Limited. Meyertech are committed to continuous product development and therefore reserve the right to change specification without notice.

TS-ZVK-66-20110901 Web: www.meyertech.co.uk Tel: +44(0)161 643 7956 Email: sales@meyertech.co.uk © Meyertech Limited 201